

Lot	Description
1	Kolding 5111 portable hygienic stainless steel pump on a mobile trolley. 1" inlet and outlet. All stainless steel construction. The supply for this pump can be either 240V or 380V to 415V. Machine size: 800mm x 360mm x 950mm high, approx. weight 100kg. CHECKED/TESTED/RUNNING *S/N HK/3* (Location Fli ...[more]
2	Posimat Posiflex F 23 VA G stainless steel rotary bottle unscrambler with speeds of up to 200 bottles per minute dependant on bottle size. Can be used on plastic bottles. Bottle dimensions: 26mm-50mm diameter x 70mm-140mm height on round bottles, 30 x 20 - 70 x 50 cross section x 70mm-140mm height. ...[more]
3	BFB MS500 compact design stretch banding machine. Maximum output 30 bundles per minute. Carton sizes: 50mm-300mm long, 15mm-330mm wide, 12mm-100mm high. Bundle sizes: 60mm-330mm long, 50mm-300mm wide, 30mm-200mm high. PE film, roll width 50mm-500mm, maximum roll diameter 300mm. Machine size: 2300mm ...[more]
4	Bosch checkweigher with a weighing range of 5gm to 300gm. Belt width 100mm. Infeed and outfeed conveyors 1600mm long, weigh cell conveyor 240mm long. Output up to 200 cartons per minute. Direction left to right. Machine size: 1600mm x 800mm x 1900mm high, approx. weight 100kg. CHECKED/TESTED/RUNNING ...[more]
5	Posimat Posipuck 5 unscrambler designed to unscramble glass or plastic bottles and place into pucks. Machine currently set up for three bottle sizes 75ml/150ml/250ml, at speeds up to 4,500 bottles per hour. Ideally suited for unstable bottles or to increase flexibility and the speed of line format c ...[more]
6	Morton 250 litre GL55 Gridlap Series 5 mixer for food and non-food pastes, compounds and powders. Duplex mixing with all stainless steel contact parts with s/s grid type beaters designed for minimal bruising or streaking of easily damaged food stuffs such as fruit. Removable blade beaters without di ...[more]
7	Mono progressive cavity pump model K63. All stainless steel contact parts for hygienic applications. 3.1A/2hp electric gear motor max 1425 rpm. 400/440V 3ph. Max pressure 3.5 bar and flow rate 1600 ltrs per hour. 2 inch diameter inlet and outlet connections. Machine size: 1400mm x 500mm x 500mm high ...[more]
8	WAM TX screw elevator for powders. All stainless steel contact parts. Mounted on a robust stainless steel frame, mobile on wheels. Machine size: 2100mm x 1250mm x 2200mm high, approx. weight 200kg. CHECKED/TESTED/RUNNING *S/N 01TX110017458* (Location Flint UK) Mfd 2011
9	Ronchi Rotomatic high speed single bowl bottle unscrambler. Stainless steel construction. Protective plexiglass casing. Quick changeover. Rotary disc style sorter. Symmetrical or asymmetrical shapes. Full safety enclosure. Highly flexible and capable of handling a diversified range of sizes and bott ...[more]
10	CMC 8 head vacuum filler, current format parts for 30ml, user friendly and very accurate filling system. Includes 3 x 24 litre header tanks on a s/s stand. Machine sizes: filler 1850mm x 1070mm x 1450mm high, approx. weight 300kg; stand containing header tanks 1080mm x 700mm x 1100mm high, approx. ...[more]
11	Italdibipack 4225 Heated impulse L sealer blade. Adjustable packing table to accommodate different pack sizes. Adjustable film rack to accommodate different widths of film. Fixed stand with lockable wheels. Machine size: 1250mm x 800mm x 1160mm high, approx. weight 90kg. CHECKED/TESTED/RUNNING *S/N ...[more]

12	Purdy Gravfil semi automatic twin head vacuum liquid filler. Stainless steel contact parts. Variable filling speed control by restricting vacuum. Repeat filling accuracy of +/- 1ml. Can be adjusted to fill any size bottle as the volume is controlled by the depth of the nozzle in the bottle neck. Eas ...[more]
13	Multipack FRB500 box former. Fully guarded, automatic former for cardboard boxes and trays. Up to 20-50 boxes per minute and up to 40 trays per minute both depending on size and material thickness. Max size of formed boxes 300mm length x 250mm width. Power: 11kW/400v, 3PH, 50-60Hz with 6 bar air pre ...[more]
14	Pester PEWO-pack 450 SN stretch banding machine with shrink tunnel unit. Adjustable for various bundle sizes. Stainless Steel and Aluminium anodized construction. The PEWO-pack 450 SN has been designed for stretch banding of different types of collations such as cartons, stacks of paper, bottles, et ...[more]
15	Marchesini MT1000 Rigid Tube Filler. Automatic filling and sealing of rigid tubes. Suitable to introduce and count tablets into plastic or metallic rigid tubes. Final tube closure with pressure cap and discharge of the correctly filled tubes onto a bucket conveyor at machine outfeed. Extremely compa ...[more]
16	King SC15 - 16 channel slat counter for tablets or capsules. Complete with missing tablet scan and auto bottle rejection. Rebuilt in 2009 by Logic TPS. CE marked. All stainless steel construction. Machine size: 2100mm x 1500mm x 2000mm high, approx. weight 1500kg. CHECKED/TESTED/RUNNING *S/N SC15-18 ...[more]
17	Countec CT-SG-120 Silica Gel desiccant inserting machine. Machine size: 1000mm x 800mm x 1950mm high, approx. weight 110kg. SOLD AS SEEN *S/N CT-G-149* (Location Flint UK) Mfd 2009
18	LP Packaging Ltd C20 Vertical case packer for small/medium sized products. Speed: up to 17 cases per minute depending on dimensions of products/containers. Precision shaping of cardboard/paperboard box (material: cardboard case, also known as American case), products (bottles, containers etc.) are f ...[more]
19	Logic Top-Cert Machine - SOLD AS SEEN (Location Flint UK)
20	Nordson Series 3100 hot melt applicator. Electric operation 3100V/200-240 AC, designed for high-line speeds. Controls melt adhesive flow to setpoint temperatures selected by the operator. System heat rate is 3.6kg/hour. Operating temperature range from 70 deg C to 230 deg C (max) with tank capacity ...[more]
21	Harland Sirius MK5 Front and Back Labeller. All s/s construction front and back labeller with scroll infeed, centralisation wheel, top hold conveyor, after wipe rollers, fully guarded. Mobile on wheels. Left to right infeed. 90mm wide plastic slat conveyor. Max label height 150mm. Min label height 3 ...[more]
22	Purdy Bancroft 6 head automatic in-line filler with 1 ltr and 2 ltr pistons (maximum capacity 2 ltr). Fully guarded with outlet for extraction unit. Separate control panel. All stainless steel contact parts. Approximate speed 30 to 50 bottles per minute depending on container type and filling materi ...[more]
23	Masterfil Single head liquid filler. 160ml piston. Mounted product hopper. Foot pedal control. Mobile on wheels. All S/S construction. Machine size: 1100mm x 700mm x 2100mm high, approx. weight 250kg. CHECKED/TESTED/RUNNING. To view a video of this machine running: <a href="https://youtu.be/l9nv21_O4jE">https://youtu.be/l9nv21_O4jE</a> *S/N ...[more]
24	Arca Etichette Wind Top label applicator with Argus Laetus coder, L150/250 performance, air reject system and pattern matching sensor. All S/S construction. Fully adjustable. Max speed 1200 labels per minute. Minimum label width 12mm and maximum label width 246mm. Accuracy 0.3mm. Maximum dispensing ...[more]

25	Klockner model EAS 1001 Unit-Dose blister packaging machine designed for pharmaceutical and nutraceutical applications. Well suited for clinical trials and stability testing. Capable of running vinyl, polypropylene and aluminium. Produces up to 80 blister packs per minute depending on blister size. ...[more]
26	BBK RS1 front and back labeller with wrap around unit. Maximum label height 150mm. Comes with variable speed conveyor, chain aligners, gating system and top stabilisers. 400V/3PH/1.5KW. Output up to 100 products per minute. Machine size: 2800mm x 1600mm x 2100mm high, approx. weight 250kg. SOLD AS S ...[more]
27	ALS 206 Top label applicator designed to apply self-adhesive labels and booklet labels to the top of a range of flat packs. Recently used for blisters. Product (such as blisters etc.) are hand loaded into the automatic feeder and are then transported by the flighted belt conveyor to the ALS206 label ...[more]
28	Kecol H100 compressed air reciprocating pump for transfer of low viscosity liquids and oils. Robust construction in stainless steel. Max operating air pressure to 100 PSI. Built in air motor and pneumatic valve delivers fluid on both up and down stroke. 60mm pump shaft with PTFE seals can be easily ...[more]
29	Universal Easifill twin head semi-automatic vacuum liquid filler. Fitted with an R7VL vacuum pump with no moving parts. Fully enclosed fan cooled (TEFC) 1/3 hp electric motor. Oil reservoir at top of machine for ease of visual check. Filling nozzles are spring loaded. Manual included. Machine size: ...[more]
30	Burnley Packaging PE500/300 Semi automatic heat shrink sealer. Can be used with PVC and PE shrink film. Mesh belt 1000mm long x 460mm wide. Machine size: 1220mm x 1000mm x 1500mm high, approx. weight 100kg. CHECKED/TESTED/RUNNING *S/N 2766* (Location Flint UK)
31	Romaco Unipac Silver 90 combined plastic and metal tube filler. Speeds of up to 5,000 tubes per hour, approx. 80 tubes per minute. Auto cassette infeed and integrated tube orientation. No tube no fill device. PLC control with single nozzle filling on a 12 station turret with adjustable filling strok ...[more]
32	Purex 9000/400 digital fume extractor. Includes volume sensing for laser, inkjet printing and coding machines. This unit ensures effective airflow and filtration of particulates up to 99.8% to 0.3 microns. Built in carbon filters remove harmful gasses and vapours. Ideal for laboratory and cleanroom ...[more]
33	Ariane MC Series 4535 compact semi automatic L sealer with heat shrink tunnel. Sealing frame 400mm (W) x 460mm (D); tunnel aperture 400mm (W) x 195mm (H); tunnel length 600mm. Speed adjustable conveyor and manual height adjustment for various product packs. Movable on lockable castors. Power supply ...[more]
34	Konrad electronics testing station for ultrasonic testing of PXI 32/64bit circuit boards. Testing for current, voltage, frequency accuracy +/- 0.001mm. Equipment includes Ultrasonic Testing Press (USP-750); Controller Unit (MP54); Generator Unit (SG3510); Converter (SE3502) and Sonotrode for welding ...[more]
35	Komax Sosei test unit for assembly of non-pressurised, metered dose drug delivery containers with automated heat stake welding facility. An integral manually operated press completes the assembly with Siemens control unit. Welding head allows for change of tooling with switchable control software. L ...[more]
36	MAR M19-4R/9PV monoblock filler/capper. Max speed up to 80 bottles per minute, depending on bottle size and product. Fill range from 5ml and currently set up with four 30ml filling pistons. Single capping head last used for 28mm screw caps. Includes change parts for 43mm dia bottles. Siemens OPIC PC ...[more]
37	Klockner model EAS Unit-Dose blister packaging machine designed for pharmaceutical and nutraceutical applications. Capable of running vinyl, polypropylene and aluminium. Produces up to 80 blister packs per minute depending on blister size. Cycles per minute: min 15 - max 90. All stainless steel cons ...[more]

38	PD20A-BSS-AAA 2" double diaphragm pump. Air operated. Stainless steel wet side with PTFE bonded diaphragms and PTFE balls. Ported 2" bsp metallic pump with flow rate of approx. 0-35.22m3/hour. Head 0-84 mtrs. Suction lift at 8 mtrs and max air pressure 8.4Kg/cm2. Mobile on wheels. Machine size: 500m ...[more]
39	Hibar Systems 4F1 Precision metering pump designed for excellent accuracy fluid dispensing, especially for analysis instruments. Full technical specs for Hibar Precision Metering Pumps: <a href="http://www.fillers.co.uk/_assets/client/images/collateral/Pump%20Technical%20Data.pdf">http://www.fillers.co.uk/_assets/client/images/collateral/Pump%20Technical%20Data.pdf</a> . CHECKED/TESTED/RUNNING. To ...[more]
40	Mettler-Toledo Garvens XS2 high speed checkweigher for continuous weighing and sorting. Capacity 0–400g. Operation from left to right with maximum through-put up to 65 weighings/minute for bottled liquids up to 120mm diameter. The electro-magnetic force weighing system is digital, temperature stable ...[more]
42	Freund-Vector USA model HCT-48 wet vacuum coating unit. Batch size 5kg to 7 kg. Spray gun system. All stainless steel construction. Variable speed pan with baffles. Inlet air damper/in-feed pump. Air handling unit. Bottom discharge system. Steam pressure: 3 Bar. Compressed air: 6 Bar. Electric suppl ...[more]
43	Interpac Waldner TS6030 tray sealer for single cavity PET trays. Currently set for trays of the following size: 325mm x 265mm x 60mm depth. Speed 20 to 24 trays per minute. Siemens SIMATIC S7-300 PLC. Danfoss frequency control. Equipped with WITT – GASETECHNIK, model KM-100 3M SO mixer for 2 defined ...[more]
44	Linx Xymark 300 SL Laser Coder. Compact, fully featured mid-powered laser coder with alphanumeric, graphics and bar code printing capability. Ideal for wide range of marking and coding tasks on primary packaging, capable of printing on both stationary and moving products with large screen area that ...[more]
45	Zalkin CA4 automatic rotary ROPP capper. Output speeds of up to 120 bottles per minute. All stainless steel construction. Bottles are fed into the machine via the in-feed timing scroll which spaces the bottles prior to them being capped. Complete with integrated cap sorting bowl and cap chute. 2.0 m ...[more]
46	Bausch & Stroebel RVS 8000 automatic rotary 8 head screw capper. All stainless steel construction. Fully guarded with clear perspex doors. Comes complete with separate control panel, cap hopper and elevator, vibratory bowl and cap infeed chute. Scroll infeed. Maximum speed 15,000 bottles per hou ...[more]
47	Manesty Express 25 station rotary EU B type tablet press. Single-sided machine fitted with one station of pre-compression and rotary feeder. This machine was overhauled in 2000 and further new parts were fitted in 2013 including cams, turret table and bearings, compression rolls, feeder bottom plate ...[more]
48	Bausch & Stroebel automatic rotary 8 head screw capper. All stainless steel construction. Fully guarded with clear perspex doors. Comes complete with separate control panel, cap hopper and elevator, vibratory bowl and cap infeed chute. Scroll infeed. Max speed 15,000 bottles per hour/250 bottles ...[more]
49	Herma 132 M Series high speed wrap around labeller. Its continuously rotating star wheel is designed for heavy-duty operation of up to 400 products per minute. Especially suitable for long, low labels. Siemens touch screen HMI. Markem Imaje Smartdate 3 thermal transfer coder. Last used on 50mm high ...[more]
50	Tolke (Germany) rotary bottle unscrambler. Star wheel with 44 pockets. Currently set up for bottle diameter of 45mm (1 set of format parts). Maximum speed of up to 120 bottles per minute. Double drop zone, the bottles drop from the belt at two opposite sides and give room for the next bottle in moti ...[more]
51	Uhlmann C-100 horizontal cartoner for bottles. Speeds of up to 100 cartons per minute, depending on bottle size. Variable speed drive. Inch button. Product size range: length 70mm - 150mm, width 30mm - 100mm, height 15mm - 85mm. GUK FA 21/4 Cartonac 91 leaflet folder. Leaflet form format: minimum 80 ...[more]

53	600L Jacketed Vessel. Stainless Steel jacketed blending vessel with hinged lid, two infeed ports, bladed stirrer and 2 inch diameter product outlet. CHECKED/TESTED/RUNNING (Location Flint UK)
54	Seidenader V90-AVSB/60-LR visual inspection machine capable of speeds of up to 150 objects per minute. Has star wheel tray infeed and straight line discharge to tray. Can be tooled for ampoules, vials, infusion bottles, cartridges, prefilled syringes, and diagnostic tubes of all sizes between 0.5ml ...[more]
55	Garvens SL2PM Check Weigher. All Stainless Steel construction. Equipped with a high-precision load cell, capable of weighing products up to 400g. Exceptionally reliable for weighing products on an extremely precise conveyor system. Digital display. Emergency stop button. This machine has three parts ...[more]
56	Complete Seitz filling line for 650ml and 1,000ml glass bottles. In full working condition, last filling a vitamin nutrition product. Line speed 40 bottles per minute. SEN Depalletiser and bottle sorter. SEN 12 head rotary pressure filler, year 1988. SEN ROPP capper, year 1988, last used on 28mm dia ...[more]
57	Pauer Tamper Evident/Vignette Labeller. 3 labelling heads: 1 top print and apply with Avery Dennison App 312 head and 2 additional Avery Dennison heads for applying tamper evident/safety proof label on each end of the box. Siemens Simatic HMI. Speeds of up to 60 per minute. Mobile on wheels. Last us ...[more]
58	DNC L35CS Case Sealer. Case taper for top sealing only. Fully guarded with two access doors (one each side). Fully adjustable both width and height for various case sizes. Box guide plate. Box tail closer. Mobile on wheels with adjustable height legs. Infeed conveyor with gating system and guide rai ...[more]
60	Marchesini MA50 Horizontal Cartoner. Automatic intermittent motion horizontal cartoning machine. Product infeed chain designed to be connected to various available automatic feeding units. Simultaneous adjustment of all infeed buckets (related to product width). Simplified magazine guide and pickup ...[more]
63	IWKA model BP20i blister packing machine. Track set up 285mm wide with 4 lines per track. Film width 0.75mm. Loop unwind system. Flat bed die cutting. Flighted exit conveyor 237mm wide x 137mm high with 50mm flights. Emboss Coder. 400volts 21kw 60hz 29amps. EXCELLENT CONDITION - Mfd 2005
64	IMA TR-135 Continuous motion automatic medium production speed blister packaging machine for pharmaceutical solid dose. Designed for production cycles that require frequent size changeovers. Suitable for the following materials (depending on set up): forming materials Alu, PP, PVC, PVC/PVDC, PVC/Acl ...[more]
65	Masterfil Mastercap single head pick and place screw capper. Year 2001. Fully automatic inline capper suitable for medium to large batch production environments. Last run on 5ltr and 10ltr containers. Standard features: easily adjustable variable torque by magnetic clutch; press-on cap chucks; inlin ...[more]
66	Manesty tablet coater - Model Accela Cota 150. All stainless steel construction. Working capacity approx 150kg (depending upon product). Drum diameter 1220mm. Drum opening 482mm. Drum speed mechanically variable 3-17rpm. Drive motor 1.5kW. With a fully perforated drum, and unique spray gun and mixin ...[more]
67	Masterfil volumetric 6 head liquid filler. Currently fitted with 500ml pistons and can handle low to high viscosity liquids. The nozzles are adjustable to fill foaming and non-foaming products with variable speed filling capacity. The honed 316L Stainless Steel filling pumps can be specified in sing ...[more]
68	Manesty 24 tablet coater - Model Accela Cota 10. The Manesty 24, can be updated to accept interchangeable drums for 2kg and 5kg. The current drum is a 12kg. All Stainless Steel product contact surfaces. Located in Aylesbury UK. SOLD AS SEEN